

XEN NIBR LASER 66140XNL

XENARC NIGHT BREAKER LASER | Xenon headlight lamps



Product family benefits

- More light allows to see further and therefore react faster
- Better visibility
- Close to laser look
- Signs, obstacles and hazards can be recognized sooner
- Premium quality made in Germany

Product family features

- Up to 200% more brightness compared to the minimum legal standard
- Up to 250 m long beam
- Up to 20% whiter light compared to the minimum legal standard
- Optimized light distribution for higher performance
- Original Spare Part Quality that exceeds all ECE minimum standards

Product datasheet

Technical data

Electrical data

Power input	35 W		
Nominal voltage	85.0 V		
Nominal wattage	35.00 W		
Power input tolerance	±3 %		
Test voltage	13.5 V		

Photometrical data

Luminous flux	3200 lm
Color temperature	4600 K

Dimensions & weight

Length	83.0 mm
Diameter	9 mm
Product weight	60.00 g

Additional product data

Base (standard designation)	PK32d-2

Certificates & standards

ECE category	D1S ¹⁾
--------------	-------------------

 $^{^{1)}}$ To be operated only with approved electronic control gear

Country specific categorizations

Order reference	66140XNL
Order reference	OOITOXINE

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899992870	XEN NIBR LASER 66140XNL	Folding carton box 1	53 mm x 46 mm x 93 mm	0.23 dm ³	79.96 g
4052899992887	XEN NIBR LASER 66140XNL	Shipping carton box 4	112 mm x 97 mm x 101 mm	1.10 dm ³	352.00 g
4052899582477	XEN NIBR LASER 66140XNL	Shipping carton box 48	- x - x -		
4052899993013	XEN NIBR LASER 66140XNL	Hard Cover Box 2	114 mm x 48 mm x 106 mm	0.58 dm ³	212.08 g
4052899993020	XEN NIBR LASER 66140XNL	Shipping carton box 10	257 mm x 129 mm x 121 mm	4.01 dm ³	1140.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Compared to minimum ECE R98/R99 requirements

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.